



tesaflex® 4251

Product Information

Multipurpose Soft PVC Tape

Product Description

tesaflex® 4251 is a specially formulated soft PVC tape with good film flexibility and natural rubber adhesive. tesaflex® 4251 is universally applicable, though it is exceptionally qualified for applications in electric installation work, repairing, splicing, or bundling. The PVC-backing makes for high durability strength, and the natural rubber adhesive ensures a high adhesion to various surfaces. tesaflex® 4251 is available in many colors: black, white, blue, yellow, red, green, grey and transparent.

Benefits:

- Flexible soft PVC backing for excellent conformability
- Good adhesion to a wide variety of surfaces
- Multiple bright colors available for color-coding applications

Application Fields

- The multipurpose soft PVC Tape is suitable for electric installation work, repairing, splicing, or bundling
- Available in multiple bright colors, tesaflex® 4251 can also be used for marking and color-coding

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | PVC film | • Total thickness | 200 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | |
|--------------------|-----------|
| • Tensile strength | 27.4 N/cm |
|--------------------|-----------|



tesaflex[®] 4251

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04251>